

Air Conditioning Technical Data

FXLQ-P



- > FXLQ20P2VEB
- > FXLQ25P2VEB
- > FXLQ32P2VEB
- > FXLQ40P2VEB
- > FXLQ50P2VEB
- > FXLQ63P2VEB



TABLE OF CONTENTS

FXLQ-P

1	Features	2
2	Specifications	3
	Technical Specifications	3
	Electrical Specifications	3
3	Electrical data	5
4	Safety device settings	6
5	Options	7
6	Capacity tables	8
	Cooling Capacity Tables	8
	Heating Capacity Tables	9
7	Dimensional drawings	10
8	Centre of gravity	12
9	Piping diagrams	13
10	Wiring diagrams	14
	Wiring Diagrams - Single Phase	14
11	Sound data	15
	Sound Pressure Spectrum	15

1 Features

For perimeter zone air conditioning

- Unit can be installed as free standing model by use of optional back plate
- Its low height enables the unit to fit perfectly beneath a window
- Stylish modern casing finished in pure white (RAL9010) and iron grey (RAL7011) blends easily with any interior
- Requires very little installation space
- Wall mounted installation facilitates cleaning beneath the unit where dust tends to accumulate
- Wired remote control can easily be integrated in the unit



Inverter



Home leave operation



Fan only



Auto cooling-heating changeover



Fan speed steps



Dry programme



Air filter



Weekly timer



Infrared remote control



Wired remote control



Centralised control



Auto-restart



Self diagnosis



Multi tenant

2 Specifications

2-1 Technical Specifications					FXLQ20P	FXLQ25P	FXLQ32P	FXLQ40P	FXLQ50P	FXLQ63P
Cooling capacity	Sensible capacity	Nom.	kW	1.70	2.10	2.50	3.10	3.90	4.90	
	Latent capacity	Nom.	kW	0.500	0.700	1.10	1.40	1.70	2.20	
	Total capacity	Nom.	kW	2.2 (1)	2.8 (1)	3.6 (1)	4.5 (1)	5.6 (1)	7.1 (1)	
Heating capacity	Total capacity	Nom.	kW	2.5 (2)	3.2 (2)	4.0 (2)	5.0 (2)	6.3 (2)	8.0 (2)	
Power input - 50Hz	Cooling	Nom.	kW	0.05 (1)		0.09 (1)		0.11 (1)		
	Heating	Nom.	kW	0.05 (2)		0.09 (2)		0.11 (2)		
Power input - 60Hz	Cooling	Nom.	kW	0.05 (1)		0.08 (1)		0.11 (1)		
	Heating	Nom.	kW	0.05 (2)		0.08 (2)		0.11 (2)		
Dimensions	Unit	Height	mm	600						
		Width	mm	1,000		1,140		1,420		
		Depth	mm	232						
	Packed unit	Height	mm	720						
		Width	mm	1,128		1,268		1,548		
		Depth	mm	346						
Weight	Unit		kg	27		32		38		
	Packed unit		kg	32		37		43		
Casing	Colour			Fresh white (RAL9010) / Dark grey (RAL7011)						
Heat exchanger	Rows	Quantity		3						
	Fin pitch		mm	1.50						
	Face area		m²	0.159		0.200		0.282		
	Stages	Quantity		14						
	Fin	Type		Cross fin coil						
Fan	Type			Sirocco fan						
	Air flow rate - 50Hz	Cooling	High	m³/min	7		8	11	14	16
			Low	m³/min	6.0		8.5		11.0	12.0
Fan motor	Drive			Direct drive						
Air filter	Type			Resin net						
Sound power level	Cooling	High	dBA	54			57	58	59	
Sound pressure level	Cooling	Medium	dBA	-						
		High	dBA	35		38	39	40		
		Low	dBA	32		33	34	35		
	Heating	High	dBA	35		38	39	40		
		Low	dBA	32		33	34	35		
Refrigerant	Type			R-410A						
	GWP			2,087.5						
	Control			Electronic expansion valve						
Piping connections	Liquid	Type		Flare connection						
		OD	mm	6,35				9,52		
	Gas	Type		Flare connection						
		OD	mm	12.7				15.9		
	Drain			O.D. 21 (Vinyl chloride)						
	Heat insulation			Glass Fiber/Urethane Foam						
	Sound absorbing insulation			Glass fiber / Urethane foam						
Safety devices	Item	01		Fuse						
		02		Fan motor thermal protection						
Control systems	Infrared remote control			BRC4C65						
	Wired remote control			BRC1H519W/S/K / BRC1D52 / BRC1E53A / BRC1E53B / BRC1E53C						
	Simplified wired remote control for hotel applications			-						
2-2 Electrical Specifications					FXLQ20P	FXLQ25P	FXLQ32P	FXLQ40P	FXLQ50P	FXLQ63P
Power supply	Name			VE						
	Phase			1~						
	Frequency		Hz	50/60						
	Voltage		V	220-240/220						
Voltage range	Max.		%	10						
	Min.		%	-10						

2 Specifications

2-2 Electrical Specifications				FXLQ20P	FXLQ25P	FXLQ32P	FXLQ40P	FXLQ50P	FXLQ63P
Current - 50Hz	Minimum circuit amps (MCA)		A	0.3		0.6			
	Maximum fuse amps (MFA)		A	15					
	Full load amps (FLA)	Total	A	0.2		0.5			
Current - 60Hz	Minimum circuit amps (MCA)		A	0.3 (3)		0.5 (3)		0.6 (3)	
	Maximum fuse amps (MFA)		A	15.0 (3)					
	Full load amps (FLA)	Total	A	0.2 (3)		0.4 (3)		0.5 (3)	

Notes

(1) Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB; equivalent piping length: 7.5m (horizontal)

(2) Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 7.5m (horizontal)

(3) Contains fluorinated greenhouse gases

Capacities are net, including a deduction for cooling (an addition for heating) for indoor fan motor heat.

Voltage range: units are suitable for use on electrical systems where voltage supplied to unit terminal is not below or above listed range limits.

Maximum allowable voltage range variation between phases is 2%.

MCA/MFA: $MCA = 1.25 \times FLA$

$MFA \leq 4 \times FLA$

Next lower standard fuse rating minimum 15A

Select wire size based on the value of MCA

Instead of a fuse, use a circuit breaker



3 Electrical data

3 - 1 Electrical Data

FXLQ-P

Units				Power supply		IFM		Input (W)	
Model	Hz	Volts	Voltage range	MCA	MFA	KW	FLA	Cooling	Heating
FXNQ20P	50	220-240	Max. 264 Min. 198	0.3	15	0.015	0.2	49	49
FXNQ25P				0.3	15	0.015	0.2	49	49
FXNQ32P				0.6	15	0.025	0.5	90	90
FXNQ40P				0.6	15	0.025	0.5	90	90
FXNQ50P				0.6	15	0.035	0.5	110	110
FXNQ63P				0.6	15	0.035	0.5	110	110

SYMBOLS

MCA : Min. Circuit Amps. (A)
 MFA : Max. Fuse Amps. (See note 5)
 kW : Fan Motor Rated Output (kW)
 FLA : Full Load Amps. (A)
 IFM : Indoor Fan Motor

NOTES

- Voltage range
Units are suitable for use on electrical systems where voltage supplied to unit terminals is not below or above listed range limits.
- Maximum allowable voltage unbalance between phases is 2%
- MCA/MFA
 $MCA + 1.25 \times FLA$
 $MFA \leq 4 \times FLA$
 (next lower standard fuse rating. Min. 15A)
- Select wire size based on the MCA.
- Instead of fuse, use Circuit Breaker.



4D034579E

4 Safety device settings

4 - 1 Safety Device Settings

4

FXLQ-P

		FXLQ20P	FXLQ25P	FXLQ32P	FXLQ40P	FXLQ50P	FXLQ63P
PC BOARD FUSE		250V 5A					
FAN MOTOR THERMAL PROTECTOR	°C	OFF: 135 ^{±10} / ON: 120 or less					

3D034529G



5 Options

5 - 1 Options

FXLQ-P

Option kit	Product name	Availability					
		FXLQ20P2VEB FXLQ25P2VEB	FXLQ32P2VEB FXLQ40P2VEB	FXLQ50P2VEB FXLQ63P2VEB	FXNQ20P2VEB FXNQ25P2VEB	FXNQ32P2VEB FXNQ40P2VEB	FXNQ50P2VEB FXNQ63P2VEB
Wired remote control	BRC1D52/BRC1E53A7(5) BRC1E53B7(6)/BRC1E53C7(7)(8)	✓	✓	✓	✓	✓	✓
Wireless remote control HP	BRC4C65	✓	✓	✓	✓	✓	✓
Wireless remote control CO	BRC4C66	✓	✓	✓	✓	✓	✓
Simplified remote control (with operation mode selector button)	BRC2E52C(2)(8)	✓	✓	✓	✓	✓	✓
Simplified remote control (without operation mode selector button)	BRC3E52C(2)(8)	✓	✓	✓	✓	✓	✓
Remote control for hotel use	BRC3A61	✓	✓	✓	✓	✓	✓
Adaptor for wiring	KRP1B61	✓	✓	✓	✓	✓	✓
Wiring adaptor for electrical appendices 1	KRP2A51	✓	✓	✓	✓	✓	✓
Wiring adaptor for electrical appendices 2	KRP4A51	✓	✓	✓	✓	✓	✓
Remote sensor	KRC501-1	✓	✓	✓	✓	✓	✓
Central remote control	DCS302B51	✓	✓	✓	✓	✓	✓
Electrical box with earth terminal (2 blocks)	KJB212A	✓	✓	✓	✓	✓	✓
Electrical box with earth terminal (3 blocks)	KJB311A	✓	✓	✓	✓	✓	✓
Unified ON/OFF controller	DCS301BA51	✓	✓	✓	✓	✓	✓
Noise filter (for electromagnetic interface only)	KEK26-1	✓	✓	✓	✓	✓	✓
Schedule timer	DST301BA51	✓	✓	✓	✓	✓	✓
External adaptor for outdoor unit (installation on indoor unit)	DTA104A61	✓	✓	✓	✓	✓	✓
Long-life replacement filter	KAFJ361K28	✓	×	×	×	×	×
Long-life replacement filter	KAFJ361K45	×	✓	×	×	×	×
Long-life replacement filter	KAFJ361K71	×	×	✓	×	×	✓
Rear decoration panel	EKRD25A9	✓	×	×	×	×	×
Rear decoration panel	EKRD40A9	×	✓	×	×	×	×
Rear decoration panel	EKRD63A9	×	×	✓	×	×	×
Multi-tenant	EKMTAC	✓	✓	✓	✓	✓	✓
Digital input adaptor	BRP7A51(3)(4)	✓	✓	✓	✓	✓	✓

This kit contains parts to connect with 10 multi-tenant indoor units.
Included languages are:

Language pack 1: English, German, French, Dutch, Spanish, Italian, and Portuguese.

With PC cable EKPCAB3 in combination with the Updater PC software, you can additionally change the language to:

Language pack 2: English, Bulgarian, Croatian, Czech, Hungarian, Romanian, and Slovenian.

Language pack 3: English, Greek, Polish, Russian, Serbian, Slovak, and Turkish.

Only possible in combination with remote control BRC2/3E52C, BRC1E53A/B/C7.

Requires installation box for adaptor PCB

Included languages are: English, German, French, Italian, Spanish, Portuguese, and Dutch.

Included languages are: English, Czech, Croatian, Hungarian, Slovenian, Romanian, and Bulgarian.

Included languages are: English, Russian, Greek, Turkish, Polish, Albanian, and Slovak.

Language pack 3 of controller BRC1E53C7 is different from that of controller BRC2/3E52C7.

4D082403

3D102604

6 Capacity tables

6 - 1 Cooling Capacity Tables

FXLQ-P

TC: Total capacity; kW
SHC: Sensible heat capacity; kW

Unit size	Indoor air temp.													
	14.0 °CWB		16.0 °CWB		18.0 °CWB		19.0 °CWB		20.0 °CWB		22.0 °CWB		24.0 °CWB	
	20.0 °CDB		23.0 °CDB		26.0 °CDB		27.0 °CDB		28.0 °CDB		30.0 °CDB		32.0 °CDB	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
20	1.5	1.3	1.8	1.5	2.1	1.7	2.2	1.7	2.3	1.7	2.4	1.6	2.4	1.5
25	1.9	1.6	2.3	1.8	2.6	2.0	2.8	2.1	3.0	2.1	3.0	2.0	3.1	1.9
32	2.4	2.1	2.9	2.2	3.4	2.5	3.6	2.5	3.8	2.5	3.9	2.4	4.0	2.3
40	3.0	2.5	3.6	2.7	4.2	3.1	4.5	3.1	4.7	3.2	4.9	3.1	5.0	2.9
50	3.8	3.0	4.5	3.4	5.2	3.8	5.6	3.9	5.9	4.0	6.0	3.8	6.2	3.6
63	4.8	3.7	5.7	4.2	6.6	4.8	7.1	4.9	7.5	4.9	7.7	4.7	7.8	4.3

CA03A095



6 Capacity tables

6 - 2 Heating Capacity Tables

FXLQ-P

Unit size	Indoor air temp. °CDB					
	16.0 kW	18.0 kW	20.0 kW	21.0 kW	22.0 kW	24.0 kW
20	2.6	2.6	2.5	2.4	2.3	2.2
25	3.4	3.4	3.2	3.1	3.0	2.8
32	4.2	4.2	4.0	3.9	3.7	3.5
40	5.2	5.2	5.0	4.8	4.7	4.4
50	6.6	6.6	6.3	6.1	5.9	5.5
63	8.4	8.4	8.0	7.7	7.5	7.0

CA03A095





7 Dimensional drawings


7 - 1 Dimensional Drawings

7

FXLQ20-25P





Required installation space




Item	Name	Description
1	Liquid pipe connection	Ø6.4 Flare connection
2	Gas pipe connection	Ø12.7 Flare connection
3	Drain pipe connection	O.D.Ø21
4	Switch box	
5	Air filter	

3TW32294-1

FXLQ32-40P



Required installation space




Item	Name	Description
1	Liquid pipe connection	Ø6.4 Flare connection
2	Gas pipe connection	Ø12.7 Flare connection
3	Drain pipe connection	O.D.Ø21
4	Switch box	
5	Air filter	

3TW32314-1

7 Dimensional drawings

7 - 1 Dimensional Drawings

FXLQ50-63P




3TW32334-1

8 Centre of gravity

8 - 1 Centre of Gravity

FXLQ-P




Model	A	B
FXLQ 20, 25 P	500	81
FXLQ 32, 40 P	588	89
FXLQ 50, 63 P	728	99

4TW32299-2

9 Piping diagrams

9 - 1 Piping Diagrams

FXLQ-P



Applicable model

FXC, FXM, FXL, FXN
 FXH, FXK, FXS, FJSP
 CBXLS, FXSP, FXCP
 FZSP, FXNP, FJNP
 FHQ, FXA, FXMQ, FBQ
 FXAQ, FXSP ~ BA, FAQ, FCQ
 FZSP ~ BA (N), FSSP ~ BA
 FQSP ~ BAN, FXUQ, FZCP, FZAP
 FXSQ ~ PV2S, FXSQ ~ T, FXSP ~ CA (N)
 FZSP ~ CA (N), FQSP ~ CAN
 FSSP ~ CA, FXSP ~ AA, FSSFP ~ AA


4D034245R

10 Wiring diagrams

10 - 1 Wiring Diagrams - Single Phase

10

FXLQ-P



Indoor unit	
A1P	Printed circuit board
C1	Capacitor (M1F)
F1U	Fuse (B , 5A, 250V)
F2U	Field Fuse
HAP	Light emitting diode (service monitor green)
K1R-K3R	Magnetic relay (M1F)
M1F	Motor (indoor fan)
Q1M	Thermo switch (M1F embedded)
Q1DI	Earth Leak Detector
R1T	Thermistor (air)
R2T-R3T	Thermistor (coil)
T1R	Transformer (220-240V/22V)
X1M	Terminal block (power supply)
X2M	Terminal block (control)
Y1E	Electronic expansion valve
Wired remote control	
R1T	Thermistor (air)
SS1	Select switch (main/sub)
Connector optional accessory	
X18A	Connector (wiring adapter for electrical appendices)

Colors	
BLK	: Black
BLU	: Blue
BRN	: Brown
ORG	: Orange
PNK	: Pink
RED	: Red
WHT	: White
YLW	: Yellow

2D077874

NOTES

- When using the central remote control see manual for connection to the unit.
- When connecting the input wires from outside, forced "OFF" or "ON/OFF" operation can be selected by the remote control. See installation manual for more details.
- Use copper conductors only.


	: Terminal block		: Connector
	: Field wiring		: Terminal
L	: Live		: Protective earth (screw)
N	: Neutral		
	: Connector		

11 Sound data

11 - 1 Sound Pressure Spectrum

FXLQ20,25P

4D034528A



NOTES

- 1 Over all (dB):
(B, G, N is already rectified)

Scale	220V		240V	
	H	L	H	L
A	35	32	37	34
C	40	36.5	42	38.5


- 2 Measuring place: Anechoic chamber

- 3 Operating conditions:

- Power source: 220•240V/220V 50/60Hz
- JIS standard

○ — 220V
○ - - - 240V


- 4 Location of microphone



- 5 Operating noise differs with operation and ambient conditions.

FXLQ32P

4D034564A



NOTES

- 1 Over all (dB):
(B, G, N is already rectified)

Scale	220V		240V	
	H	L	H	L
A	35	32	37	34
C	39	37	41	39


- 2 Measuring place: Anechoic chamber

- 3 Operating conditions:

- Power source: 220•240V/220V 50/60Hz
- JIS standard

○ — 220V
○ - - - 240V


- 4 Location of microphone



- 5 Operating noise differs with operation and ambient conditions.

FXLQ40P

4D034565A



NOTES

- 1 Over all (dB):
(B, G, N is already rectified)

Scale	220V		240V	
	H	L	H	L
A	38	33	40	35
C	42	38	44	40


- 2 Measuring place: Anechoic chamber

- 3 Operating conditions:

- Power source: 220•240V/220V 50/60Hz
- JIS standard

○ — 220V
○ - - - 240V


- 4 Location of microphone



- 5 Operating noise differs with operation and ambient conditions.

FXLQ50P

4D034566A



NOTES

- 1 Over all (dB):
(B, G, N is already rectified)

Scale	220V		240V	
	H	L	H	L
A	39	34	41	36
C	44	38.5	46	40.5


- 2 Measuring place: Anechoic chamber

- 3 Operating conditions:

- Power source: 220•240V/220V 50/60Hz
- JIS standard

○ — 220V
○ - - - 240V

- 4 Location of microphone




- 5 Operating noise differs with operation and ambient conditions.

11 Sound data

11 - 1 Sound Pressure Spectrum

11



© LUNDA

Daikin Europe N.V. Naamloze Vennootschap - Zandvoordestraat 300, B-8400 Oostende - Belgium - www.daikin.eu - BE 0412 120 336 - RPR Oostende



EEDEN19 04/19



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V.. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.